

# Safety Data Sheet

## CARBOGRIP 75 ML

Safety Data Sheet dated 28/6/2018, version 3

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Mixture identification:

Trade name: CARBOGRIP 75 ML

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Technical product

Uses advised against:

do not use on humans and animals

#### 1.3. Details of the supplier of the safety data sheet

Company:

STAC PLASTIC SPRAY S.R.L. Via E. De Nicola 9/11 10036 Settimo Torinese (To) Italia.

STAC PLASTIC SPRAY S.R.L. Tel. n.. +39 011 8977566 Fax n. +39 011 8977491

Competent person responsible for the safety data sheet:

Montini Vittorino stacplas@stacplastic.com

#### 1.4. Emergency telephone number

STAC PLASTIC SPRAY S.R.L. Tel. n.. +39 011 8977566 Fax n. +39 011 8977491

---

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):



Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.



Warning, Skin Irrit. 2, Causes skin irritation.



Warning, STOT SE 3, May cause drowsiness or dizziness.



Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

#### 2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

## Safety Data Sheet

### CARBOGRIP 75 ML

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P391 Collect spillage.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contains

hydrocarbons c7, n-alkanes, isoalkanes, cyclics

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

section 10.3

## SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

| Qty               | Name                                               | Ident. Number                                                                | Classification                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------|----------------------------------------------------|------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| >= 25% -<br>< 30% | hydrocarbons c7, n-alkanes,<br>isoalkanes, cyclics | EC: 927-510-4<br>REACH No.: 01-<br>2119666169-<br>27-0000                    |  2.6/2 Flam. Liq. 2 H225<br> 3.2/2 Skin Irrit. 2 H315<br> 4.1/C2 Aquatic Chronic 2 H411<br><br> 3.10/1 Asp. Tox. 1 H304<br> 3.8/3 STOT SE 3 H336 |
| >= 20% -<br>< 25% | GPL                                                | CAS: 68476-40-4<br>EC: 270-681-9<br>REACH No.: 01-<br>2119486557-<br>22-XXXX |  2.5/C Press. Gas (Comp.)<br>H280<br> 2.2/1 Flam. Gas 1 H220<br>DECLK (CLP)*                                                                                                                                                                                                                                                                                                                                    |
| >= 7% -<br>< 10%  | xylene                                             | Index<br>number: 601-022-00-9<br>CAS: 1330-20-7<br>EC: 215-535-7             |  2.6/3 Flam. Liq. 3 H226<br> 3.1/4/Inhal Acute Tox. 4 H332<br> 3.1/4/Dermal Acute Tox. 4<br>H312<br> 3.2/2 Skin Irrit. 2 H315                                                                                                         |
| >= 1% -<br>< 3%   | ethylbenzene                                       | Index<br>number: 601-023-00-4<br>CAS: 100-41-4<br>EC: 202-849-4              |  3.8/3 STOT SE 3 H335<br> 2.6/3 Flam. Liq. 3 H226<br> 3.10/1 Asp. Tox. 1 H304<br> 3.1/4/Inhal Acute Tox. 4 H332<br> 3.3/2 Eye Irrit. 2 H319      |

## Safety Data Sheet

### CARBOGRIP 75 ML

|                   |         |                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-------------------|---------|--------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                   |         |                                                              |  3.2/2 Skin Irrit. 2 H315<br> 3.9/2 STOT RE 2 H373                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| >= 0.5%<br>- < 1% | toluene | Index number: 601-021-00-3<br>CAS: 108-88-3<br>EC: 203-625-9 |  2.6/2 Flam. Liq. 2 H225<br> 3.7/2 Repr. 2 H361<br> 3.10/1 Asp. Tox. 1 H304<br> 3.9/2 STOT RE 2 H373<br> 3.2/2 Skin Irrit. 2 H315<br> 3.8/3 STOT SE 3 H336 |

\*DECLK (CLP): This substance is classified in accordance with Note K, Annex VI of EC Regulation CE 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 (Table 3.1) or the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

#### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

#### In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

### 4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects due to the contained substances see chapter 11

### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

Follow the doctor's instructions.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:  
water jets.

### 5.2. Special hazards arising from the substance or mixture

## Safety Data Sheet

### CARBOGRIP 75 ML

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

#### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

#### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

#### 6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

#### 6.4. Reference to other sections

See also section 8 and 13

---

## SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

#### 7.2. Conditions for safe storage, including any incompatibilities

store in a cool, well ventilated place, away from heat, flames, sparks or other sources of ignition

keep only in the original container away from sunlight neighborhoods

avoid contact with skin and eyes, inhalation of vapours/mists/dusts.

do not use empty containers before they are cleaned.

contaminated clothing must be replaced before entering the dining areas.

at work do not eat or drink.

avoid the accumulation of electrostatic charges.

do not smoke

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

#### 7.3. Specific end use(s)

None in particular

---

**SECTION 8: Exposure controls/personal protection**

8.1. Control parameters

hydrocarbons c7, n-alkanes, isoalkanes, cyclics

TLV TWA - 400ppm-1639,26 mg/m<sup>3</sup>

TLV STEL - 500ppm-2049,08 mg/m<sup>3</sup>

VLE 8h - 2085 mg/m<sup>3</sup>-500ppm

xylene - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

ethylbenzene - CAS: 100-41-4

EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

toluene - CAS: 108-88-3

EU - TWA(8h): 192 mg/m<sup>3</sup>, 50 ppm - STEL: 384 mg/m<sup>3</sup>, 100 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss

DNEL Exposure Limit Values

hydrocarbons c7, n-alkanes, isoalkanes, cyclics

Worker Professional: 300 mg/kg/d - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 2085 mg/l - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 149 mg/kg/d - Exposure: Human Oral - Frequency: Long Term, systemic effects

xylene - CAS: 1330-20-7

Worker Professional: 180 mg/kg/d - Consumer: 108 mg/kg/d - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 77 mg/l - Consumer: 14.8 mg/l - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg/d - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 289 mg/kg/d - Exposure: Human Inhalation - Frequency: Short Term (acute)

PNEC Exposure Limit Values

xylene - CAS: 1330-20-7

Target: Fresh Water - Value: 0.32 mg/l

Target: Marine water - Value: 0.32 mg/l

Target: Freshwater sediments - Value: 12.46 mg/l

Target: Marine water sediments - Value: 12.46 mg/l

Target: Soil (agricultural) - Value: 2.31 mg/kg

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

## Safety Data Sheet

### CARBOGRIP 75 ML

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

Do not expose to temperatures exceeding 50° c.

Environmental exposure controls:

None

Appropriate engineering controls:

None

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

| Properties                                    | Value               | Method: | Notes: |
|-----------------------------------------------|---------------------|---------|--------|
| Appearance and colour:                        | Spray can           | --      | --     |
| Odour:                                        | characteristic      | --      | --     |
| Odour threshold:                              | Not Relevant        | --      | --     |
| pH:                                           | Not Relevant        | --      | --     |
| Melting point / freezing point:               | Not Relevant        | --      | --     |
| Initial boiling point and boiling range:      | Not Relevant        | --      | --     |
| Flash point:                                  | < 0 ° C             | --      | --     |
| Evaporation rate:                             | Not Relevant        | --      | --     |
| Solid/gas flammability:                       | Not Relevant        | --      | --     |
| Upper/lower flammability or explosive limits: | Not Relevant        | --      | --     |
| Vapour pressure:                              | 4 bar +/- 1         | --      | --     |
| Vapour density:                               | > 2                 | --      | --     |
| Relative density:                             | 0.773 kg/l +/- 0.05 | --      | --     |
| Solubility in water:                          | undissolvable       | --      | --     |
| Solubility in oil:                            | complete            | --      | --     |
| Partition coefficient (n-octanol/water):      | Not Relevant        | --      | --     |
| Auto-ignition temperature:                    | >200°C              | --      | --     |
| Decomposition temperature:                    | Not Relevant        | --      | --     |
| Viscosity:                                    | Not Relevant        | --      | --     |
| Explosive properties:                         | section 10.3        | --      | --     |
| Oxidizing properties:                         | Not Relevant        | --      | --     |

### 9.2. Other information

| Properties                           | Value                                 | Method: | Notes: |
|--------------------------------------|---------------------------------------|---------|--------|
| kinematic viscosity:                 | kv > 2,05 mm <sup>2</sup> /s (a 40°C) | --      | --     |
| Miscibility:                         | N.A.                                  | --      | --     |
| Fat Solubility:                      | complete                              | --      | --     |
| Conductivity:                        | Not Relevant                          | --      | --     |
| Substance Groups relevant properties | Not Relevant                          | --      | --     |

# Safety Data Sheet

## CARBOGRIP 75 ML

---

### SECTION 10: Stability and reactivity

- 10.1. Reactivity  
avoid contact with strong acids and bases and oxidizing agents.
- 10.2. Chemical stability  
Stable under normal conditions
- 10.3. Possibility of hazardous reactions  
avoid mixing the product with strong oxidizers and strong acids  
may form explosive vapor / air mixtures in places not well ventilated
- 10.4. Conditions to avoid  
avoid the accumulation of electrostatic charges.  
keep away from heat, sources of ignition
- 10.5. Incompatible materials  
acids, alkalis and alkaline metals  
oxidizing agents
- 10.6. Hazardous decomposition products  
the product is flammable, following combustion can lead to the formation of dangerous decomposition products  
by thermal decomposition can rid COx

---

### SECTION 11: Toxicological information

- 11.1. Information on toxicological effects  
Toxicological information of the product:  
N.A.  
Toxicological information of the main substances found in the product:  
hydrocarbons c7, n-alkanes, isoalkanes, cyclics
  - a) acute toxicity:  
Test: LC50 - Route: Inhalation - Species: Rat > 23300 mg/m3 - Duration: 4h  
Test: LD50 - Route: Skin - Species: Rat > 2920 mg/kg  
Test: LD50 - Route: Oral - Species: Rat > 5840 mg/kg  
GPL - CAS: 68476-40-4
  - a) acute toxicity:  
Test: LC50 - Route: Inhalation - Species: Rat > 658 mg/l  
xylene - CAS: 1330-20-7
  - a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Mouse = 5627 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit > 5000 ml/kg  
Test: LC50 - Route: Inhalation - Species: Rat = 6700 Ppm - Duration: 4h
  - g) reproductive toxicity:  
Test: Reproductive Toxicity - Species: Rat = 500 Ppm  
ethylbenzene - CAS: 100-41-4
  - a) acute toxicity:  
Test: LC50 - Route: Inhalation - Species: Mouse = 35500 mg/m3  
Test: LC50 - Route: Inhalation - Species: Rat = 55000 mg/m3  
Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg  
xylene - CAS: 1330-20-7  
LD50 (RAT) ORAL: 5000 MG/KG
  - ethylbenzene - CAS: 100-41-4  
LD50 (RAT) ORAL: 3500 MG/KG  
LD50 (RAT) ORAL: 4710 MG/KG BW

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

## Safety Data Sheet

### CARBOGRIP 75 ML

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.  
hydrocarbons c7, n-alkanes, isoalkanes, cyclics

#### a) Aquatic acute toxicity:

Endpoint: EL50 - Species: Fish = 1.5 mg/l - Duration h: 48

Endpoint: LC50 - Species: Daphnia = 4 mg/l - Duration h: 24

GPL - CAS: 68476-40-4

#### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish Negative 19 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia Negative 14.2 mg/l - Duration h: 48

Endpoint: EL50 - Species: Algae Negative 7.7 mg/l - Duration h: 96

xylene - CAS: 1330-20-7

#### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EL50 - Species: Daphnia = 1 mg/l - Duration h: 24

Endpoint: EL50 - Species: Algae = 4.36 mg/l - Duration h: 76

#### b) Aquatic chronic toxicity:

Endpoint: NOEL - Species: Fish > 1.3 mg/l - Duration h: 56 - Notes: giorni

### 12.2. Persistence and degradability

None

xylene - CAS: 1330-20-7

Biodegradability: Not persistent and Biodegradable - Test: N.A. - Duration: N.A. - %:

N.A. - Notes: N.A.

ethylbenzene - CAS: 100-41-4

Biodegradability: Not persistent and Biodegradable - Test: N.A. - Duration: N.A. - %:

N.A. - Notes: N.A.

### 12.3. Bioaccumulative potential

xylene - CAS: 1330-20-7

Bioaccumulation: Not bioaccumulative - Test: N.A. N.A. - Duration: N.A. - Notes: N.A.

ethylbenzene - CAS: 100-41-4

Bioaccumulation: Not bioaccumulative - Test: N.A. N.A. - Duration: N.A. - Notes: N.A.

### 12.4. Mobility in soil

xylene - CAS: 1330-20-7

Mobility in soil: Mobile - Test: N.A. N.A. - Duration: N.A. - Notes: N.A.

ethylbenzene - CAS: 100-41-4

Mobility in soil: Mobile - Test: N.A. N.A. - Duration: N.A. - Notes: N.A.

### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

### 12.6. Other adverse effects

None

---

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

## Safety Data Sheet

### CARBOGRIP 75 ML

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Additional disposal information:

contaminated packaging should be sent for recovery or disposal in compliance with national regulations on waste management

reuse if possible. Product residues are to be considered hazardous waste. disposal must be entrusted to authorised waste management, in compliance with national and, where appropriate, local.

---

#### SECTION 14: Transport information

- 14.1. UN number
  - ADR-UN number: 1950
  - IATA-Un number: 1950
  - IMDG-Un number: 1950
- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
  - ADR-Class: 2.5°F CAP. 2.2.2.1.6 UN1950
  - IATA-Class: 2.1
  - IMDG-Class: 2 Aerosols UN 1950
- 14.4. Packing group
- 14.5. Environmental hazards
  - Marine pollutant: Marine pollutant
- 14.6. Special precautions for user
  - IMDG-Page: 2102
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
  - No

---

#### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
  - Dir. 98/24/EC (Risks related to chemical agents at work)
  - Dir. 2000/39/EC (Occupational exposure limit values)
  - Regulation (EC) n. 1907/2006 (REACH)
  - Regulation (EC) n. 1272/2008 (CLP)
  - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
  - Regulation (EU) 2015/830
  - Regulation (EU) n. 286/2011 (ATP 2 CLP)
  - Regulation (EU) n. 618/2012 (ATP 3 CLP)
  - Regulation (EU) n. 487/2013 (ATP 4 CLP)
  - Regulation (EU) n. 944/2013 (ATP 5 CLP)
  - Regulation (EU) n. 605/2014 (ATP 6 CLP)
  - Regulation (EU) n. 2015/1221 (ATP 7 CLP)
  - Regulation (EU) n. 2016/918 (ATP 8 CLP)
  - Regulation (EU) n. 2016/1179 (ATP 9 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
  - None
- Where applicable, refer to the following regulatory provisions :
  - Directive 2012/18/EU (Seveso III)
  - Regulation (EC) nr 648/2004 (detergents).
  - Dir. 2004/42/EC (VOC directive)
- Provisions related to directive EU 2012/18 (Seveso III):
  - Seveso III category according to Annex 1, part 1
  - Product belongs to category: P3a, E2

## Safety Data Sheet

### CARBOGRIP 75 ML

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

### SECTION 16: Other information

Text of phrases referred to under heading 3:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H411 Toxic to aquatic life with long lasting effects.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H280 Contains gas under pressure; may explode if heated.

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H312 Harmful in contact with skin.

H335 May cause respiratory irritation.

H319 Causes serious eye irritation.

H373 May cause damage to organs (hearing organs) through prolonged or repeated exposure.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

| Hazard class and hazard category | Code         | Description                                                    |
|----------------------------------|--------------|----------------------------------------------------------------|
| Flam. Gas 1                      | 2.2/1        | Flammable gas, Category 1                                      |
| Aerosols 1                       | 2.3/1        | Aerosol, Category 1                                            |
| Press. Gas (Comp.)               | 2.5/C        | Gases under pressure (Compressed gas)                          |
| Flam. Liq. 2                     | 2.6/2        | Flammable liquid, Category 2                                   |
| Flam. Liq. 3                     | 2.6/3        | Flammable liquid, Category 3                                   |
| Acute Tox. 4                     | 3.1/4/Dermal | Acute toxicity (dermal), Category 4                            |
| Acute Tox. 4                     | 3.1/4/Inhal  | Acute toxicity (inhalation), Category 4                        |
| Asp. Tox. 1                      | 3.10/1       | Aspiration hazard, Category 1                                  |
| Skin Irrit. 2                    | 3.2/2        | Skin irritation, Category 2                                    |
| Eye Irrit. 2                     | 3.3/2        | Eye irritation, Category 2                                     |
| Repr. 2                          | 3.7/2        | Reproductive toxicity, Category 2                              |
| STOT SE 3                        | 3.8/3        | Specific target organ toxicity - single exposure, Category 3   |
| STOT RE 2                        | 3.9/2        | Specific target organ toxicity - repeated exposure, Category 2 |
| Aquatic Chronic 2                | 4.1/C2       | Chronic (long term) aquatic hazard, category 2                 |

Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

SECTION 4: First aid measures

SECTION 5: Firefighting measures

SECTION 6: Accidental release measures

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection

SECTION 9: Physical and chemical properties

SECTION 10: Stability and reactivity

SECTION 11: Toxicological information

SECTION 12: Ecological information

## Safety Data Sheet

### CARBOGRIP 75 ML

SECTION 13: Disposal considerations  
 SECTION 14: Transport information  
 SECTION 15: Regulatory information  
 SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

| Classification according to Regulation (EC) Nr. 1272/2008 | Classification procedure |
|-----------------------------------------------------------|--------------------------|
| Aerosols 1, H222+H229                                     | On basis of test data    |
| Skin Irrit. 2, H315                                       | Calculation method       |
| STOT SE 3, H336                                           | Calculation method       |
| Aquatic Chronic 2, H411                                   | Calculation method       |

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
 Commission of the European Communities  
 SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van  
 Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
 CAS: Chemical Abstracts Service (division of the American Chemical Society).  
 CLP: Classification, Labeling, Packaging.  
 DNEL: Derived No Effect Level.  
 EINECS: European Inventory of Existing Commercial Chemical Substances.  
 GefStoffVO: Ordinance on Hazardous Substances, Germany.  
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.  
 IATA: International Air Transport Association.  
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
 ICAO: International Civil Aviation Organization.  
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).  
 IMDG: International Maritime Code for Dangerous Goods.  
 INCI: International Nomenclature of Cosmetic Ingredients.  
 KSt: Explosion coefficient.  
 LC50: Lethal concentration, for 50 percent of test population.  
 LD50: Lethal dose, for 50 percent of test population.  
 PNEC: Predicted No Effect Concentration.  
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.  
 STEL: Short Term Exposure limit.  
 STOT: Specific Target Organ Toxicity.  
 TLV: Threshold Limiting Value.  
 TWA: Time-weighted average  
 WGK: German Water Hazard Class.

**Safety Data Sheet**  
**CARBOGRIP 75 ML**